



# Safety Data Sheet

## Professional Wall and Ceiling Texture Spray

Date of issue: 05/01/2017

Supersedes: All

Version: 1a

### SECTION 1: Identification

#### 1.1. Product identifier

Product name	Wall and Ceiling Textures
Product Identifiers	Sudden Bond Professional Wall Texture, Sudden Bond Professional Ceiling Texture, Sudden Bond Professional Fine Ceiling Texture
Other means of identification	Spray Texture

#### 1.2. Recommended uses and restrictions

Uses	Decorative, interior wall and ceiling textures for new construction or remodeling/repairs. Use per manufacturer's recommendations.
Restrictions	Avoid breathing dust, avoid skin contact, use in well ventilated area, interior use only.

#### 1.3. Manufacturer/Supplier Information

Solid Products, Inc.  
3290 Industrial Rd.  
PO Box 97  
Richfield, WI 53076  
T 262-628-3840  
www.solidproductsinc.com

#### 1.4. Emergency telephone number

Emergency number : 262-628-3840

### SECTION 2: Hazards Identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Carc. 1A H350  
STOT RE 2 H373

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H350 - May cause cancer (Inhalation) H373 - May cause damage to organs (lungs) through prolonged or repeat exposure (inhalation)
Precautionary statements (GHS-US)	: P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P260 - Do not breathe dust P280 - Wear appropriate personal protective equipment P308+P313 - IF exposed or concerned: Get medical advice/attention P314 - Get medical advice and attention if you feel unwell P501 - Dispose of contents/container to comply with local/regional/national international regulations Store in a cool, dry place away from direct sunlight or excessive heat.

#### 2.3. Other hazards

Other hazards not contributing to the classification	: Other constituents in this product are considered nuisance particles or dust. Exposure to dusts or powders may cause mechanical irritation of the respiratory system, eyes, and skin. . Particulates Not Otherwise Regulated (Respirable Fraction) has an OSHA PEL of 5 mg/m <sup>3</sup> (15 mppcf) TWA and ACGIH Guideline of 3 mg/m <sup>3</sup> TWA. Particulates Not Otherwise Regulated (Total Dust) has an OSHA PEL of 15 mg/m <sup>3</sup> (50 mppcf) TWA and ACGIH Guideline of 10 mg/m <sup>3</sup> TWA.
--	--

#### 2.4. Unknown acute toxicity (GHS-US)

No data available

# Safety Data Sheet

## Ready Mix Joint Compound

### SECTION 3: Composition/information on ingredients

#### 3.1. Mixture

Name	Product identifier	% (weight)
Limestone	(CAS No) 1317-65-3	> 80
Also may contain any of the following:		
Kaolin	(CAS No) 1332-58-7	< 10
Attapulgate	(CAS No) 12174-11-7	< 5
Mica	(CAS No) 12001-26-2	< 10

Industrial hygiene studies did not detect airborne respirable crystalline silica during normal use. Job site air monitoring should be conducted when permissible exposure limits may be exceeded.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Immediate effects are not anticipated. If large amounts of dusts are inhaled, remove to fresh air. If breathing problems persist seek medical attention.
- First-aid measures after skin contact : Rinse skin area with mild soap and water. Seek medical attention if irritation develops or persists.
- First-aid measures after eye contact : Do not rub, rinse immediately with plenty of water. Seek medical attention if irritation develops or persists.
- First-aid measures after ingestion : Rinse mouth. Not expected to be hazardous in small amounts. Seek medical attention if problems persist.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Long-term dust exposure may aggravate pre-existing respiratory disease. Persons who develop silicosis have greatly increased risks of developing tuberculosis and workers who are exposed to crystalline silica and smoke have increased risks of lung damage.
- Symptoms/injuries after skin contact : Direct contact may cause irritation, rash or dry skin. Rubbing may intensify symptoms and create abrasions.
- Symptoms/injuries after eye contact : Particulate matter may scratch the cornea or cause other mechanical injury to the eye. Scratching or physical damage to the eyes can cause irritation, redness, pain, tear formation, blurred vision, and light sensitivity.
- Symptoms/injuries after ingestion : Ingestion is not anticipated under normal working conditions.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Any. Use media appropriate for surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Reactivity : Not reactive under normal use and conditions.

#### 5.3. Advice for firefighters

- Protection during firefighting : Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : See Section 8 for Personal Protective Equipment.

#### 6.2. Environmental precautions

Not expected to present an ecological hazard to the environment. Dispose of in accordance with local/regional/national international regulations.

#### 6.3. Methods and material for containment and cleaning up

- Vacuum spilled material with fine filter.
- Maintain proper ventilation
- Dispose of in accordance with local/regional/national international regulations.

# Safety Data Sheet

## Ready Mix Joint Compound

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid dust inhalation and contact with skin and eyes. Minimize dust generation. Wear suitable respiratory equipment as recommended.
- Hygiene measures : Practice good housekeeping. Wash thoroughly after handling. Change contaminated clothing. Do not reuse until laundered.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a cool, dry place away from direct sunlight or excessive heat. Keep container closed when not in use. Do not increase height of pallet or stack more than 2 pallets high.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Component	Exposure Limits	
	OSHA PEL (mg/m3)	ACGIH TLV (mg/m3)
Limestone	15 Total 5 Respirable	10 Total
Kaolin	15 Total 5 Respirable	2 Respirable
Attapulgite	15 Total 5 Respirable	10 Total
Mica	20 mppcf	3

#### 8.2. Exposure controls

- Appropriate engineering controls : Provide sufficient ventilation. Minimize dust production. Observe exposure limits.
- Personal protective equipment
- Hand protection : In case of repeated or prolonged contact wear suitable protective gloves
- Eye protection : Approved goggles or safety glasses.
- Skin and body protection : Under dusty conditions or when excessive skin contact is likely, wear coveralls or other suitable work clothing.
- Respiratory protection : Where exposure through inhalation may occur from use, NIOSH/MSHA approved respiratory protection is recommended. Follow OSHA 1910.134 for all respirator use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Powder
- Color : Off-White
- Odor : Low to no odor
- Odor threshold : No data available
- pH : 7 – 9
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point/Freezing point : No data available
- Boiling point : No data available
- Flash point : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : 825°C
- Flammability (solid, gas) : Not Flammable
- Vapor pressure : No data available
- Relative vapor density at 20 °C : No data available
- Relative density : .8 – 1.1 (H<sub>2</sub>O=1)
- Solubility : Soluble in water
- Viscosity : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Explosive limits : No data available
- VOC content : None

# Safety Data Sheet

## Ready Mix Joint Compound

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Not reactive under normal use and conditions.

#### 10.2. Chemical stability

Stable at normal temperatures and conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

None known

#### 10.5. Incompatible materials

Strong acids

#### 10.6. Hazardous decomposition products

Above 825°C limestone can decompose and release carbon dioxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Dust inhalation may irritate respiratory system. Long-term dust exposure may aggravate and/or result in respiratory disease.
Symptoms/injuries after skin contact	: Direct contact may cause irritation, rash or dry skin. Rubbing may intensify symptoms.
Symptoms/injuries after eye contact	: Dust may cause mechanical eye irritation.
Symptoms/injuries after ingestion	: May cause discomfort and possible abdominal obstruction.
Chronic effects	: Prolonged exposure to dust may result in lung disease.
Carcinogenicity	: This product is not expected to increase the risk of cancer.  This product may contain a small amount of crystalline silica as a naturally occurring impurity in some of the raw materials. The IARC classifies crystalline silica inhaled from occupational sources as carcinogenic to humans, Group 1. The NTP classifies respirable crystalline silica as a substance which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen.  This product may contain attapulgite. The IARC classifies attapulgite as possibly carcinogenic to humans, Group 2B. Neither the NTP or OSHA classifies attapulgite as a carcinogen.

### SECTION 12: Ecological information

#### 12.1. Toxicity

This product is not classified as environmentally hazardous

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose of in accordance with local/regional/national international regulations.

# Safety Data Sheet

Ready Mix Joint Compound

## SECTION 14: Transport information

This product is not regulated by the DOT as a hazardous material  
IATA, IMDG, ICAO, Not regulated

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Not regulated or listed under any of the following: TSCA Section 12(b) Export Notification, OSHA Specifically Regulated Substances, SARA Title III Sections 302, 304, and 313, CERCLA, RCRA, CAA Section 112, CAA Section 112(r), Safe Drinking Water Act

### 15.2. International regulations

#### CANADA WHMIS

All ingredients are included in the Canadian DSL  
Crystalline Silica: WHMIS Classification D2A

### 15.3. US State regulations


California Proposition 65 – Carcinogens: Attapulgite, Respirable crystalline silica.  
Industrial hygiene studies did not detect airborne respirable crystalline silica during normal use.

## SECTION 16: Other information

Prepared by: Solid Products, Inc.                      Effective Date: 6/1/2015  
3290 Industrial Rd.                                      Revision: 1  
PO Box 97  
Richfield, WI 53076  
(262)628-3840

NFPA health hazard : 1 - Exposure could cause irritation.  
NFPA fire hazard : 0 - Materials that will not burn.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

Hazard scale: 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Severe



#### Disclaimer:

*This information is based on data believed to be correct. This information is provided without warranty or guarantee, express or implied.*